

35667 - 16356 HWS Burgau - Abflussdrosselung am Bauwerk Bahnquerung SÜD

8 x Sonderregler Durchgangsbreite 2,50 m

OW	h ₀ (IB Obermeyer)		h _ü für Q _{unvollkommen} [nach OINF-Ber. 2021-12-15]	Stichmaß z	Q _{vollkommen}	Abminderungs- faktor κ	Q _{unvollkommen} = Q _{vollkommen} * κ	Q _{resultierend}
[mNN]	[m]	[mm]	[m]	[m]	[m³/s]	[-]	[m³/s]	[m³/s]
455,60	1,02	1020	0,84	1,05	-	-	-	-
455,68	1,10	1100	0,89	1,05	61,0	0,60	36,4	36,4
455,76	1,18	1180	0,93	1,04	59,5	0,69	41,0	41,0
455,82	1,24	1240	0,97	0,97	55,1	0,79	43,6	43,6
455,87	1,29	1290	1,01	0,92	52,1	0,89	46,2	46,2
455,95	1,37	1370	1,07	0,86	50,0	-	-	50,0
455,98	1,40	1400	1,07	0,85	50,0	-	-	50,0
456,02	1,44	1440	1,07	0,84	50,0	-	-	50,0
456,07	1,49	1490	1,07	0,83	50,0	-	-	50,0
456,10	1,52	1520	1,07	0,82	50,0	-	-	50,0
456,16	1,58	1580	1,07	0,80	50,0	-	-	50,0
456,20	1,62	1620	1,07	0,79	50,0	-	-	50,0
456,27	1,69	1690	1,07	0,77	50,0	-	-	50,0
456,28	1,70	1700	1,07	0,77	50,0	-	-	50,0
456,32	1,74	1740	1,07	0,76	50,0	-	-	50,0
456,35	1,77	1770	1,07	0,75	50,0	-	-	50,0
456,58	2,00	2000	?	0,83	58,2	-	-	58,2
456,81	2,23	2225	?	0,90	67,3	-	-	67,3

